



Environmental Services Department

Planning & Zoning Division

390 Red Cedar St., Suite C, Menomonie, WI 54751

Telephone: 715.231.6521

FAX: 715.232.4099

June 30, 2015

A private sewage system or replacement was installed on property you own during the year listed below. As per 145.245(3) Wisconsin State Statutes and Chapter 6 of the Dunn County Comprehensive Zoning Ordinance (1993), you are required to be contacted by the Dunn County Zoning Office informing you of your responsibility to provide maintenance on the system. This maintenance program requires inspection of or pumping of the private sewage system at least once every three years.

As per 83.54.4(d) 1. Except as provided in subparagraph 3, a POWTS that exists prior to July 1, 2000, and that utilizes a treatment or dispersal component consisting in part of in situ soil shall be visually inspected at least once every 3 years to determine whether wastewater or effluent from the POWTS is ponding on the surface of the ground.

Inspections shall be conducted by a licensed master plumber, licensed journeyman plumber, licensed restricted plumber or licensed septic tank pumper. The inspection shall certify that the system is in proper operating condition and the septic tank is less than 1/3 full of sludge and scum. If the inspection reveals sludge and scum volume to be greater than 1/3 the volume of the tank, the tank shall be serviced by a licensed septic tank pumper. You may choose to go directly to pumping the tank and eliminate the need for an inspection which determines if the tank needs pumping.

In either case, please return this letter within 45 days with the appropriate signatures. Septic tank maintenance will ensure maximum service life of your private sewage system and avoid premature failure and very costly replacement. **Filing of this signed letter will alert future buyers of this property, that required maintenance was or was not performed. This will be the only contact from this office.**

Inspection of the private septic system components reveal that it does require pumping at this time. Contact septic pumper for service. (PLEASE INDICATE IF PUMPING WAS COMPLETED BEFORE MAILING BACK THIS FORM)

Date of inspection _____

Signature of inspector and license number _____

I certify that the septic system on the property mentioned below is not ponding on the ground surface or backing up into the structure, and that the septic tank has been visually inspected and pumped. (To be completed by septic tank pumper only)

T. L. SINZ PLUMBING, INC.

E5609 708th AVE.

82240

Date of pumping 7/23/15

Signature of septic tank pumper and license number _____

Inspection of the private septic system components reveal that the system does not require pumping at this time.

Date of inspection _____

Signature of inspector and license number _____

RETURN TO:

Dunn County Zoning Office

390 Red Cedar St. Suite C

Menomonie, Wisconsin 54751

432414

032 291325.40302

Year of installation

or replacement

2003

Lot/CSM/Sub. & Parcel Address

ROBERT C
SMITH

N7756 510TH ST
MENOMONIE WI 54751

1 CSM #3931
N7756 510TH ST

PRIVATE SEWAGE SYSTEM INSPECTION REPORT for Dunn County

Name	Robert Smith	
Address	768 th Ave.	
City	Menomonie	
State & Zip	WI	54751

PLUMBER:		CST:	
Jack Bowman		Henry Grote	

GENERAL INFORMATION

CST BM Elev.:	Insp. BM Elev.:
BM Description: Base of flagged steel stake.	

TANK INFORMATION

TYPE	MANUFACTURER	CAPACITY
Septic	Wieser	1200
Dosing	Wieser	800

TANK SETBACK INFORMATION

TYPE	P/L	WELL	BLDG	VENT TO AIR INTAKE
Septic	>100'	96'	13'	
Dosing	>100'	100+	26'	

PUMP/SIPHON INFORMATION

Manuf/Model #		Zoeller 98	
Lift 2.5'	Friction Loss 3.9'	System Head 2.5'	TDH Ft. 8.90'
Forcemain	Length	Dia.	Dist. to Well

SOIL ABSORPTION SYSTEM

Dispersal Cell Information	Manuf.	Width 11'	Length 135'	No. of Cells 1
Setback	Type of System	P/L	Bldg	Well Lake/Stream
Information	At-Grade	>100'	35'	111'

DISTRIBUTION SYSTEM

Header/Manifold Length Dia.	Distribution pipe(s) Length 67' each Dia. 2" Spacing	X Hole Size 3/16"	X Hole Spacing 2'
--------------------------------	---	----------------------	----------------------

WI FUND: _____ Yes X No _____ Maybe COMMENTS:

REASON: _____

New House/Double Wide	<u>X</u>
New Mobile Home	
New Other	
Replace/Repair/Reconnect	

7/9/03
Date

Zabel A100 filter installed.


Alma Henrich
Inspector's Signature

220750
Cert. No.


Property Address/City	E5439 760th Ave. <u>N 7756 510th St.</u> Menomonie, WI 54751
Town of	SHERMAN
Legal	SW - SE 25-29-13
Subdivision	
CSM #	
Sanitary permit #	432414
State Plan ID #	815045
Parcel tax #	291325.40301
Computer #	032-1066-01

ELEVATION DATA

STATION	ELEVATION	ELEVATION
Benchmark		100.00
Well		
Bldg. Sewer		102.59
St/Ht Inlet		102.18
St/Ht Outlet		
Dt. Inlet		
Dt. Bottom		99.77
Header/Man		
Dist. Pipe		102.27
Bottom of system		



SHED




SHED

120 ACRE
PARCEL

B.M. BASE OF
FLAGGED STEEL STAKE
ELEV. 100'



WESER 1200/800
GAL. S.T./D.T.



GARAGE

HOUSE
EST 39
N 7756

W



SCALE: 1" = 40'

DUNN COUNTY

Parcel 291325.40301

Comp. 032-1066-01

Address _____

SANITARY PERMIT

No. 432414

NEW

OWNER BOB SMITH, 768TH AVE., MENOMONIE, WI

PLUMBER JACK BOWMAN LICENSE # 222839

TOWN OF SHERMAN LOCATED SW-SE

SECTION 25 T 29 N - R 13 W

AND/OR LOT _____ BLOCK _____

_____ SUBDIVISION

Janet Riedel AUTHORIZED ISSUING OFFICER - DATE 4/30/03

CHAPTER 145.135 WISCONSIN STATUTES

- (a) The purpose of the sanitary permit is to allow installation of the private sewage system described in the application for permit.
 - (b) The approval of the sanitary permit is based on regulations on force on the date of issue.
 - (c) The sanitary permit is valid 2 years from original date of issuance and may be renewed for similar periods thereafter. Application for renewal shall be made through the county and shall comply with regulations in effect at the time.
 - (d) Changed regulations will not impair the validity of a sanitary permit until the time of renewal.
 - (e) Renewal of the sanitary permit will be based on regulations in force at the time renewal is sought. Changed regulations may impede renewal.
 - (f) The sanitary permit is transferable. A sanitary permit transfer shall be obtained from the county authority.
- * If you wish to renew the permit, or transfer ownership of the permit, please contact the county authority.

THIS PERMIT EXPIRES 4/30/05 UNLESS RENEWED BEFORE THAT DATE

(TWO YEARS FROM THE ORIGINAL DATE OF ISSUANCE)

SBD-6453 (R. 08/92)

VISIBLE FROM THE ROAD FRONTING THE LOT
DURING CONSTRUCTION



Safety and Buildings Division
201 W. Washington Ave., P.O. Box 7162
Madison, WI 53707 - 7162
(608) 266-3151

County

Dunn

Sanitary Permit Number (to be filled in by Co.)

432414

Sanitary Permit Application

In accord with Comm 83.21, Wis. Adm. Code, personal information you provide may be used for secondary purposes Privacy Law, s15.04(1)(m)

State Plan I.D. Number

trans id 815045

Project Address (if different than mailing address)

291325.40301

I. Application Information - Please Print All Information

Property Owner's Name

Bob Smith

Property Owner's Mailing Address

768th Ave.

City, State

Menomonee, WI

Zip Code

54751

Phone Number

715/235-6451

Parcel #

Lot #

Block #

Property Location

SW 1/4, SE 1/4, Section 25

T 29 N; R 13 W (circle one)

Subdivision Name

CSM Number

City Village Township of

Sherman

II. Type of Building (check all that apply)

☒ 1 or 2 Family Dwelling - Number of Bedrooms

4

☐ Public/Commercial - Describe Use

☐ State Owned - Describe Use

III. Type of Permit: (Check only one box on line A. Complete line B if applicable)

A. ☒ New System ☐ Replacement System ☐ Treatment/Holding Tank Replacement Only

☐ Other Modification to Existing System

B. ☐ Permit Renewal Before Expiration ☐ Permit Revision ☐ Change of Plumber ☐ Permit Transfer to New Owner

List Previous Permit Number and Date Issued

IV. Type of POWTS System: (Check all that apply)

☐ Non-Pressurized In-Ground ☐ Mound \geq 24 in. of suitable soil ☐ Mound $<$ 24 in. of suitable soil ☒ At-Grade ☐ Single Pass Sand Filter ☐ Constructed Wetland ☐ Pressurized In-Ground ☐ Holding Tank ☐ Peat Filter ☐ Aerobic Treatment Unit ☐ Recirculating Sand Filter ☐ Recirculating Synthetic Media Filter ☐ Leaching Chamber ☐ Drip Line ☐ Gravel-less Pipe ☐ Other (explain)

V. Dispersal/Treatment Area Information:

Design Flow (gpd) 600 Design Soil Application Rate (gpd/sf) 0.5 Dispersal Area Required (sf) 900 1200 Dispersal Area Proposed (sf) 900 1215 System Elevation 101.3' contour

VI. Tank Info	Capacity in Gallons		Total Gallons	Number of Units	Manufacturer	Prefab Concrete	Site Constructed	Steel	Fiber Glass	Plastic
	New Tanks	Existing Tanks								
Septic or Holding Tank	1800	+	1800	1	Wheeler Concrete	X				
Aerobic Treatment Unit										
Dosing Chamber	800	+	800		Combination	X				

II. Responsibility Statement- I, the undersigned, assume responsibility for installation of the POWTS shown on the attached plans.

Plumber's Name (Print)

Jack A. Bowman

Plumber's Signature

Jack A. Bowman

MP/MPRS Number

MP 222839

Business Phone Number

715/235-4634

Plumber's Address (Street, City, State, Zip Code)

2819 Knappa St, Menomonee, WI 54751

VIII. County/Department Use Only

☒ Approved

☐ Disapproved

☐ Owner Given Reason for Denial

Sanitary Permit Fee (includes Groundwater Surcharge Fee)

300

Date Issued

4-30-03

Issuing Agent Signature (No Stamps)

Jack A. Bowman

IX. Conditions of Approval/Reasons for Disapproval

032-1066-01

Attach complete plans (to the County only) for the system on paper not less than 8 1/2 x 11 inches in size

April 30, 2003

CUST ID No.222839

ATTN: POWTS Inspector

JACK A BOWMAN
BOWMAN PLUMBING, INC.
2819 KNAPP ST
MENOMONIE WI 54751

ZONING OFFICE
DUNN COUNTY SPIA
800 WILSON AVE
MENOMONIE WI 54751

CONDITIONAL APPROVAL
PLAN APPROVAL EXPIRES: 04/30/2005

SITE:

Bob Smith Residence
760TH Ave
Town of Sherman, 54751
Dunn County
SW1/4, SE1/4, S25, T29N, R13W

FOR:

Description: Four Bedroom At-grade System
Object Type: POWT System Regulated Object ID No.: 883319
Revision

Identification Numbers
Transaction ID No. 863598 Site ID No. 653803
Please refer to both identification numbers, above, in all correspondence with the agency.

The submittal described above has been reviewed for conformance with applicable Wisconsin Administrative Codes and Wisconsin Statutes. The submittal has been **CONDITIONALLY APPROVED**. The owner, as defined in chapter 101.01(10), Wisconsin Statutes, is responsible for compliance with all code requirements.

The following conditions shall be met during construction or installation and prior to occupancy or use:

General Approval Requirements:

- This system is to be constructed and located in accordance with the enclosed approved plans and with the "At-grade Component Manual Using a Pressure Distribution System for Private Onsite Wastewater Systems" SBD-10570-P (R.6/99) and the SSWMP Publication 9.6 Design of Pressure Distribution Networks for ST_SAS (01/81)
- Per manual cited above, limited activities are allowed in the area 15 feet down slope of the component area. Soil compaction, excavation, vehicular traffic and other similar activities that impact the treatment and dispersal are prohibited.
- The well must be a minimum of 25 feet from any POWTS tank, and a minimum of 50 feet from the absorption area. chs. NR 811 & 812c
- A Sanitary Permit must be obtained from the county where this project is located in accordance with the requirements of Sec. 145.135 and 145.19, Wis. Stats.
- Inspection of the private sewage system installation is required. Arrangements for inspection shall be made with the designated county official in accordance with the provisions of Sec. 145.20(2)(d), Wis. Stat
- Comm 83.22(7) A copy of the approved plans, specifications and this letter shall be on-site during construction and open to inspection by authorized representatives of the Department, which may include local inspectors.

Conditional
APPROVED
DEPARTMENT
DIVISION OF SAFETY
[Signature]
SEE CORRESPONDENCE

Owner Responsibilities:

- **Comm 83.52 Responsibilities.** The owner of a POWTS shall be responsible for ensuring that the operation and maintenance of the POWTS occurs in accordance with this chapter and the approved management plan under s. **Comm 83.54(1).**
- **Comm 83.52(2)** A POWTS that is not maintained in accordance with the approved management plan or as required under s. **Comm 83.54(4)** shall be considered a human health hazard.
- **Comm 83.55** The owner is responsible for submitting a maintenance verification report acceptable to the county for maintenance tracking purposes. Reports shall be submitted at intervals appropriate for the component(s) utilized in the POWTS.

All permits required by the state or the local municipality shall be obtained prior to commencement of construction/installation/operation.

In granting this approval the Division of Safety & Buildings reserves the right to require changes or additions should conditions arise making them necessary for code compliance. As per state stats 101.12(2), nothing in this review shall relieve the designer of the responsibility for designing a safe building, structure, or component.

Inquiries concerning this correspondence may be made to me at the telephone number listed below, or at the address on this letterhead.

The above left addressee shall provide a copy of this letter to the owner and any others who are responsible for the installation, operation or maintenance of the POWTS.

Sincerely,



Charles L Bratz
POWTS Reviewer II , Integrated Services
(608)789-7893 , 7:45 am - 4:30 pm Monday - Friday
cbratz@commerce.state.wi.us

Fee Required \$	60.00
Fee Received \$	60.00
Balance Due \$	0.00

WiSMART code: 7633

cc: Leroy G Jansky , Wastewater Specialist, (715) 726-2544

RECEIVED

APR 29 2003

SAFETY & BLDGS DIV.

AT-GRADE AND PRESSURE DISTRIBUTION COMPONENT DESIGN

New site for a Residential application

INDEX AND TITLE PAGE

Project name: Smith
Owner's name: Bob Smith
Owner's address: 768th Ave.
Menomonie, WI 54751
Legal description: SW, SE, S25, T29N/R 13W
Township: Sherman
County: Dunn
Subdivision name: N.A.
Lot number: N.A.
Plan transaction no: Trans. Id. No. 815045

Page 1. title page
Page 2. general infor. & lateral diagram
Page 3. At-grade views
Page 4 tank information
Page 5. pump information
Page 6 site plan
Page 7 maintenance
Page 8 management plan

Attachments: c

Designer: Ioretta / Jack A. Bowman

Date: April 28, 2003

Signature: 

License number: MP22839

Phone no. 715/235-4634

Fax no. 715/235-3650

Internet b Bowmanpb@wwt.net

tionally
OVERED
OF COMMERCE
EY AND BUILDINGS

SPONDENCE

Designed pursuant to the At-GradeComponent Manual for POWTS SDB-10570-P (R.6/99) and SSWMP Publication 9.6 design of pressure distribution networks for ST-SAS (01/81)

GENERAL INFORMATION

Residential site, four bedroom home, 600gal DWF
 Soil application rate of 0.5
 Limiting factor at 40inches
 Site area 20%
 1280/800LP Wieser Concrete tank with Orenco FT-0822 filter
 effluent quality is #1
 contour line 101.3', system lateral invert elev. 101.8'


center fed system, 2 laterals
 orifice dia. 3/16"
 orifice spacing 2ft.
 linear rate of 4.44sq.ft.

CENTER FED - LATERAL LAYOUT DIAGRAM

(not to scale)


2 laterals @ 67ft. (P)
 lateral dia. 2"
 force main dia. 2"

34 orifices per lateral = 68 total orifices
 2.5 pressure in ft., 0.66gpm for orifice
 44.88gpm total system




AT-GRADE PLAN VIEW

not to scale




A -	9
B -	135
1/6 B -	22.5
C -	11
D -	5
E -	2
L -	145
W -	21
A X B -	1215 ft ²

- total aggregate cell
A X B
- plowed area L x W



AT-GRADE CROSS SECTION




COMBINATION SEPTIC TANK/PUMP CHAMBER

(No Scale)

Approved Locking Manhole Cover
With Warning Label Attached

4"
Approved Cap,



Note: Pump and Alarm Are On Separate Circuits

Tank Manufacturer: Weiser Concrete
 Tank Size-Septic/Pump: 1200/800 Gallons
 Alarm Manufacturer: S.J. Electro
 Model Number: S-J1
 Switch Type: Mercury
 Pump Manufacturer: Zoeller
 Model Number: #98
 Minimum Discharge Rate: 44.8 GPM

Capacities: A 19 inches or 422.56 Gallons
 + B 2 inches or 44.48 Gallons
 + C 5 inches or 111.20 Gallons
 + D 10 inches or 222.40 Gallons
 Total..... = 36 inches or 800.64 Gallons

(within the tank only)
 Vertical Difference Between Pump Off and Distribution Pipe: 6.50 Feet
 Minimum Required Supply Pressure: 2.5 + 1.3 = 3.25 Feet
95 Feet of Force Main x 4.11 Friction Factor/100 Feet: +3.90 Feet
2 Inch Diameter Force Main


Total Dynamic Head: ... = 13.65 Feet

21.84 gal total tank * 5 = 109.20 gals
1 m void = 15.48 gals
20 % DWF = 120 gals

gal/in 22.24

..... ***On-Site***

~~"57" CAST IRON SERIES~~ "57" CAST IRON SERIES



Model BN53
Pictured

- BN/BE Models available packaged with a piggyback variable level float switch.
- .3 H.P., 1 Ph., 115V or 230V.
- Non-Clogging vortex impeller design.
- Passes ½ inch solids (sphere).
- 1½" NPT discharge.
- Automatic reset thermal overload protection.
- Stainless steel screws.
- Cast iron switch case, motor and pump housing.
- Engineered, glass-filled impeller with metal insert (Model 53).
- Glass-filled polypropylene base. (Model 53).
- Model 57 all cast iron construction.
- UL listed 3-wire 15 ft. standard cord.



Canadian Standards
Assoc approval
available



TOTAL DYNAMIC HEAD/CAPACITY
PER MINUTE
EFFLUENT AND DEWATERING


53-55 MODELS			
Ft.	Meters	Gal.	Ltrs.
5	1.52	43	163
10	3.05	34	129
15	4.57	19	72

Lock Valve: 19.25"

009897B

* Cast iron motor housing, pump housing and switch case.
Glass-filled polypropylene impeller and base.

"98" CAST IRON SERIES



Model BN98
Pictured

- BN/BE Models available packaged with a piggyback variable level float switch.
- ½ H.P., 1 Ph., 115V or 230V.
- Non-Clogging vortex impeller design.
- Passes ½ inch solids (sphere).
- 1½" NPT discharge. (1½" X 2" PVC adapter fitting included with BN and BE models.)
- Automatic reset thermal overload protection.
- Stainless steel screws, guard, handle.
- Watertight neoprene "□" ring between motor and pump housing.
- UL listed 3-wire 15 ft. standard cord.



Canadian Standards
Assoc approval
available




TOTAL DYNAMIC HEAD/CAPACITY
PER MINUTE
EFFLUENT AND DEWATERING

MODEL 98		60 CYCLE	
Feet	Meters	Gallons	Liters
5	1.5	72	273
10	3.1	61	231
15	4.6	45	170
20	6.1	25	95
Lock Valve:		23'	

009971E

"137" CAST IRON SERIES



Model BN137
Pictured

- BN/BE Models available packaged with a piggyback variable level float switch.
- Durable cast iron construction.
- 1 & 3 Phase models available.
(115, 200-208 & 230V - 1 Ph).
(200-208, 230 & 460V - 3 Ph).
- Non-Clogging vortex impeller design.
- Passes 5/8" solids (sphere).
- 1½" NPT discharge. (1½" X 2" PVC adapter fitting included with BN and BE models.)
- Automatic reset thermal overload protection.
- Stainless steel screws, bolts, guard, handle.
- UL listed 3-wire 15 ft. standard cord.



Canadian Standards
Assoc approval
available




TOTAL DYNAMIC HEAD/CAPACITY
PER MINUTE
EFFLUENT AND DEWATERING

MODELS 137			
Ft.	Meters	Gal.	Ltrs.
5	1.5	93	352
10	3.1	79	299
15	4.6	64	242
20	6.1	36	136
25	7.6	8	30
Lock Valve:		26"	

009921B

NOTE: No UL listing for 200-208/1Ph. pumps.



009922

TOTAL DYNAMIC HEAD/
FLOW PER MINUTE
EFFLUENT AND DEWATERING

MODEL	53,55,	98	137	140, 4140	161, 4161	163, 4163	165, 4165	185, 4185	186, 4186	188, 4188	189, 4189	191
FT. M.	GAL. LTRS.	GAL. LTRS.	GAL. LTRS.	GAL. LTRS.	GAL. LTRS.	GAL. LTRS.	GAL. LTRS.	GAL. LTRS.	GAL. LTRS.	GAL. LTRS.	GAL. LTRS.	GAL. LTRS.
5 1.52	43 163	72 273	93 352	91 344	100 379	61 231	61 231		58 220	145 549	145 549	45 170
10 3.05	34 129	61 231	79 299	84 318	93 352	61 229	61 231		58 220	140 530	140 530	45 170
15 4.57	19 72	45 170	64 242	76 288	85 322	60 227	61 231		58 220	134 507	135 511	45 170
20 6.10		25 95	36 136	68 257	79 299	59 223	60 227		58 220	128 484	131 496	45 170
25 7.62			8 30	59 223	70 265	57 216	59 223		58 220	122 462	125 473	45 170
30 9.14				49 185	62 235	55 206	58 220	85 322	58 220	116 439	120 454	45 170
40 12.19				21 79	45 170	46 172	55 206	70 265	58 220	104 394	109 413	45 170
50 15.24					20 76	33 125	50 189	51 193	58 220	90 341	97 367	45 170
60 18.29						15 57	39 148	32 121	58 220	71 269	85 322	45 170
70 21.34							23 87	9 34	52 197	51 193	69 261	45 170
80 24.38							10 38		45 170	28 106	51 193	45 170
90 27.43									31 117	2 8	34 129	45 170
100 30.48									16 60		17 64	40 151
110 32.00									4 15			30 114
120 36.58												20 76
130 39.62												10 38
LOCK VALVE:	19.25'	23'	26'	46'	56'	66'	86.5'	73'	114'	91'	110'	137'



SITE PLAN

BOWMAN PLUMBING, INC.

LEGEND

BM: 100.' base of flagged steel stake

X-pits

Scale 1"-30' except where indicated


Master Plumber # 5875

2819 Knapp Street
Menomonie, WI 54751
715-235-4634
715-235-3650 (fax)

System Elev. 101.3' contour
Pipe invert elev. 101.8'

Site is 120a.c., all lot lines greater than 100.' from system area

out buildings



Site is 1/8 mile on 760th Ave
north side of road, off of Hwy 25

PROJECT: Smith

At-grade System Maintenance and Operation Specifications

Service Provider's Name
POWTS Regulator's Name

Bowman Plumbing Inc.
Dunn County Zoning Office

Phone 715/235-4634
Phone 715/232-1401

System Flow and Load Parameters

Design Flow - Peak	600	gpd	Maximum Influent Particle Size	1/8	in
Estimated Flow - Average	400	gpd	Maximum BOD5	220	mg/L
Septic Tank Capacity	1200	gal	Maximum TSS	150	mg/L
Soil Absorption Component Size	1200	ft ²	Maximum FOG	30	mg/L
Type of Wastewater	Domestic		Maximum Fecal Coliform	>10E4	cfu/100 mL


Service Frequency

Septic and Pump Tank	Inspect and/or service once every 3 years
Effluent Filter	Inspect and clean at least once every 3 years
Pump and Controls	Test once every 3 years
Alarm	Should test monthly
Pressure System	Laterals should be flushed and pressure tested every 1.5 years
Mound	Inspect for ponding and seepage once every 3 years
Other	Initially filter should be checked yearly to determine cleaning schedule

Miscellaneous Construction and Materials Standards

1. Observation pipes are slotted and materials conform to Table Comm 84.30-1, have a watertight cap, and are secured in as shown in the at-grade component manual.
2. Dispersal cell aggregate conforms to Comm 84.30 (6)(i), Wis. Adm. Code.
3. All gravity and pressure piping materials conform to the requirements in Comm 84, Wis. Adm. Code.
4. Tillage of the basal area is accomplished with a mold board or chisel plow.
5. The at-grade structure and other disturbed areas will be seeded and mulched to prevent soil erosion and help reduce frost penetration.
6. Areas within 15 feet of the downslope toe will be protected from compaction.
7. All other construction details are as per the at-grade component manual SBD-10570-P (R. 6/99).

Lateral Turn-up Detail



At-grade System Management Plan

Pursuant to Comm 83.54, Wis. Adm. Code

General

This system shall be operated in accordance with Comm 82-84 Wis. Adm. Code, and shall be maintained in accordance with its' component manuals [SBD-10570-P (R. 06/99) and SSWMP Pub. 9.6 (01/81)] and local or state rules pertaining to system maintenance and maintenance reporting.

No one should ever enter a septic or pump tank since dangerous gases may be present that could cause death.

Septic and pump tank abandonment shall be in accordance with Comm 83.33, Wis. Adm. Code when the tanks are no longer used as POWTS components.

Septic or pump tank manhole risers, access risers and covers should be inspected for water tightness and soundness. Access openings used for service and assessment shall be sealed watertight upon the completion of service. Any opening deemed unsound, defective, or subject to failure must be replaced. Exposed access openings greater than 8-inches in diameter shall be secured by an effective locking device to prevent accidental or unauthorized entry into a tank or component.

Septic Tank

The septic tank shall be maintained by an individual certified to service septic tanks under s. 281.48, Stats. The contents of the septic tank shall be disposed of in accordance with NR 113, Wis. Adm. Code. The operating condition of the septic tank and outlet filter shall be assessed at least once every 3 years by inspection.

The outlet filter shall be cleaned as necessary to ensure proper operation. The filter cartridge should not be removed unless provisions are made to retain solids in the tank that may slough off the filter when removed from its enclosure. If the filter is equipped with an alarm, the filter shall be serviced if the alarm is activated continuously. Intermittent filter alarms may indicate surge flows or an impending continuous alarm.

The septic tank shall have its contents removed when the volume of sludge and scum in the tank exceeds 1/3 the liquid volume of the tank. If the contents of the tank are not removed at the time of a triennial assessment, maintenance personnel shall advise the owner of when the next service needs to be performed to maintain less than maximum scum and sludge accumulation in the tank.

The addition of biological or chemical additives to enhance septic tank performance is generally not required. However, if such products are used they shall be approved for septic tank use by the Department of Commerce.

Pump Tank

The pump (dosing) tank shall be inspected at least once every 3 years. All switches, alarms, and pumps shall be tested to verify proper operation. If an effluent filter is installed within the tank it shall be inspected and serviced as necessary.

At-grade and Pressure Distribution System

No trees or shrubs should be planted on the at-grade. Plantings may be made around the at-grade's perimeter, and the at-grade shall be seeded and mulched as necessary to prevent erosion and to provide some protection from frost penetration. Traffic (other than for vegetative maintenance) on the at-grade is not recommended since soil compaction may hinder aeration of the infiltrative surface within the mound and snow compaction in the winter will promote frost penetration. Cold weather installations (October-February) dictate that the at-grade be heavily mulched as protection from freezing.

Influent quality into the at-grade system may not exceed 220 mg/L BOD₅, 150 mg/L TSS, and 30 mg/L FOG for septic tank effluent or 30 mg/L BOD₅, 30 mg/L TSS, 10 mg/L FOG, and 10⁴ cfu/100 mL for highly treated effluent. Influent flow may not exceed maximum design flow specified in the permit for this installation.

The pressure distribution system is provided with a flushing point at the end of each lateral, and it is recommended that each lateral be flushed of accumulated solids at least once every 18 months. When a pressure test is performed it should be compared to the initial test when the system was installed to determine if orifice clogging has occurred and if orifice cleaning is required to maintain equal distribution within the dispersal cell.

Observation pipes within the dispersal cell shall be checked for effluent ponding. Ponding levels shall be reported to the owner, and any levels above 4 inches considered as an impending hydraulic failure requiring additional, more frequent monitoring.

Contingency Plan

If the septic tank or any of its components become defective the tank or component shall be repaired or replaced to keep the system in proper operating condition.

If the dosing tank, pump, pump controls, alarm or related wiring becomes defective the defective component(s) shall be immediately repaired or replaced with a component of the same or equal performance.

If the at-grade component fails to accept wastewater or begins to discharge wastewater to the ground surface, it will be repaired or replaced in its' present location by increasing basal area if toe leakage occurs or by renovating the biologically clogged absorption and dispersal media, installing new piping, and replacing other components as deemed necessary to bring the system into proper operating condition.

See Page 7 of this plan for the name and telephone number of your local POWTS regulator and service provider.

A week ago applied for Lanti permit
for Bob Smith as a three bedroom
system. Heres is the new paper
work as a revision as a four
bedroom system. The only change is a
3 to 4 Bedroom system *Lantia*

November 25, 2002

CUST ID No.222839

ATTN: POWTS Inspector

JACK A BOWMAN
BOWMAN PLUMBING, INC.
2819 KNAPP ST
MENOMONIE WI 54751

ZONING OFFICE
DUNN COUNTY SPIA
800 WILSON AVE
MENOMONIE WI 54751

**CONDITIONAL APPROVAL
PLAN APPROVAL EXPIRES: 11/25/2004**

SITE:

Bob Smith Residence
760TH Ave
Town of Sherman, 54751
Dunn County
SW 1/4, SE 1/4, S25, T29N, R13W

FOR:

Description: Three Bedroom At-Grade System
Object Type: POWT System Regulated Object ID No.: 883319

Identification Numbers
Transaction ID No. 815045
Site ID No. 653803
Please refer to both identification numbers, above, in all correspondence with the agency.

The submittal described above has been reviewed for conformance with applicable Wisconsin Administrative Codes and Wisconsin Statutes. The submittal has been **CONDITIONALLY APPROVED**. The owner, as defined in chapter 101.01(10), Wisconsin Statutes, is responsible for compliance with all code requirements.

The following conditions shall be met during construction or installation and prior to occupancy or use:

General Approval Requirements:

- This system is to be constructed and located in accordance with the enclosed approved plans and with the "At-grade Component Manual Using a Pressure Distribution System for Private Onsite Wastewater Systems" SBD-10570-P (R.6/99) and the "Pressure Distribution Component Manual for Private Onsite Wastewater Treatment Systems" SBD-10573-P (R.6/99).
- Per manual cited above, limited activities are allowed in the area 15 feet down slope of the component area. Soil compaction, excavation, vehicular traffic and other similar activities that impact the treatment and dispersal are prohibited.
- The well must be a minimum of 25 feet from any POWTS tank, and a minimum of 50 feet from the absorption area. chs. NR 811 & 812c
- A Sanitary Permit must be obtained from the county where this project is located in accordance with the requirements of Sec. 145.135 and 145.19, Wis. Stats.
- Inspection of the private sewage system installation is required. Arrangements for inspection shall be made with the designated county official in accordance with the provisions of Sec. 145.20(2)(d), Wis. Stat
- Comm 83.22(7) A copy of the approved plans, specifications and this letter shall be on-site during construction and open to inspection by authorized representatives of the Department, which may include local inspectors.
- The changes made to this plan on 11/25/02 by this reviewer were acknowledged and approved by the system designer.

**Conditional
APPROVED**
DEPARTMENT OF
DIVISION OF SAFETY
SEE CORRESPONDENCE

Owner Responsibilities:

- **Comm 83.52 Responsibilities.** The owner of a POWTS shall be responsible for ensuring that the operation and maintenance of the POWTS occurs in accordance with this chapter and the approved management plan under s. **Comm 83.54(1).**
- **Comm 83.52(2)** A POWTS that is not maintained in accordance with the approved management plan or as required under s. **Comm 83.54(4)** shall be considered a human health hazard.
- **Comm 83.55** The owner is responsible for submitting a maintenance verification report acceptable to the county for maintenance tracking purposes. Reports shall be submitted at intervals appropriate for the component(s) utilized in the POWTS.


All permits required by the state or the local municipality shall be obtained prior to commencement of construction/installation/operation.

In granting this approval the Division of Safety & Buildings reserves the right to require changes or additions should conditions arise making them necessary for code compliance. As per state stats 101.12(2), nothing in this review shall relieve the designer of the responsibility for designing a safe building, structure, or component.

Inquiries concerning this correspondence may be made to me at the telephone number listed below, or at the address on this letterhead.

The above left addressee shall provide a copy of this letter to the owner and any others who are responsible for the installation, operation or maintenance of the POWTS.

Sincerely,



Charles L Bratz
POWTS Reviewer II , Integrated Services
(608)789-7893 , 7:45 am - 4:30 pm Monday - Friday
cbratz@commerce.state.wi.us

Fee Required \$	175.00
Fee Received \$	175.00
Balance Due \$	0.00

WiSMART code: 7633

cc: Leroy G Jansky , Wastewater Specialist, (715) 726-2544

AT-GRADE - sloping site

Residential Application
INDEX & TITLE SHEET

Project: SMITH

Owner: Bob Smith

Address: 768th Ave.
Menomonie, WI 54751

Legal Description: SW, SE, 25, 29, 13W

Township: Sherman County: Dunn

Subdivision name: NAA.

Lot number: N.A.

Parcel ID number: _____

Plan transaction number: _____

RECEIVED

NOV 22 2002

SAFETY & BLDG DIV.

<u>Title</u>	Page <u>1 of 8</u>
<u>Worksheet</u>	Page <u>2 of 8</u>
<u>Site plan</u>	Page <u>3 of 8</u>
<u>Plan view-cross section</u>	Page <u>4 of 8</u>
<u>Piping & tank</u>	Page <u>5 of 8</u>
<u>Pump information</u>	Page <u>6 of 8</u>
<u>Management plan</u>	Page <u>7 of 8</u>
<u>Phone no.</u>	Page <u>8 of 8</u>
_____	Page _____
Attachments: <u>soil test to state's</u>	Page _____
<u>plan</u>	

Designer: loretta/Jack A. Bowman

License Number: MP 222839

Signature: 

Phone Number: (715) 235-4634

Date: Nov. 20, 2002

tionally
ROVED
IT OF COMMERCE
FTEY AND BUILDINGS

ESPONDENCE

At-Grade component manual for POWTS SBD-10570-P (R.6/99), and

SSWMP Publication 9.6 design of pressure distribution networks for ST-SAS (1/81)

At-Grade sloping site
Residential Application

Site Data

3 Bdrm - 450 gal DWF

20% slope

0.5 soil application rate

40" limiting factor

Cell Information

#1 - influent quality

120 ft. aggregate length

3.75 linear loading rate

Data Entry

Center connection

2 laterals (59 ft ea.)

2 ft. orifice spacing

3/16 dia orifice

2" dia lateral

F. M. - feet. force main to be below frost level, maintain
out to lateral (No Drain Back)

Orenco FT-0822 septic filter

Wieser 1000/600 LP tank

Tropet / Smith

SITE PLAN

BOWMAN PLUMBING, INC.

LEGEND

BM: 100.' base of flagged steel stake

X-pits


Scale 1"-30' except where indicated

Master Plumber # 5875

2819 Knapp Street
Menomonie, WI 54751
715-235-4634
715-235-3650 (fax)


System Elev. 101.3' contour
Pipe invert elev. 101.8'

Site is 120a.c., all lot lines greater than 100.' from system area




AT-GRADE PLAN VIEW

not to scale




A -	7.5 ft
B -	120.0 ft
1/6 B -	20.0 ft
C -	9.5 ft
D -	5.0 ft
E -	5.0 ft
L -	130.0 ft
W -	19.5 ft
A X B -	900. ft ²

- total aggregate cell A X B
- plowed area L x W




AT-GRADE CROSS SECTION



- 12" top soil and subsoil over aggregate and tapered to toes
- 6" aggregate below pipe(s) and 2" above pipe

PRESSURE DISTRIBUTION AND DOSE TANK



Lateral Specifications


orifice diameter (in)	<u>3/16</u> (0.188)
orifice spacing (ft)	<u>2</u>
orifices/lateral	<u>30</u>
lat. discharge rate	<u>19.80</u> (gpm)
sys. discharge rate	<u>39.60</u> (gpm)

laterals & force main of PVC Sch 40	
B - bed length	<u>60 ft.</u>
P - lateral length	<u>59 ft.</u>
connection point	<u>center</u>
number laterals	<u>2</u>
lateral diameter	<u>2</u> (in)
force main diameter	<u>2</u> (in)
force main length	<u>95</u> (ft)

TYPICAL PUMP CHAMBER LAYOUT

not to scale

weather-proof junction box



Pump manufacturer Zoeller
Pump model number # 43998

Alarm manufacturer S.J. Electro
Alarm model number S-J1

Effluent Pumps..... On-Site

"53" CAST IRON SERIES / "57" CAST IRON SERIES



Model BN53
Pictured

- BN/BE Models available packaged with a piggyback variable level float switch.
- .3 H.P., 1 Ph., 115V or 230V.
- Non-Clogging vortex impeller design.
- Passes 1/2 inch solids (sphere).
- 1 1/2" NPT discharge.
- Automatic reset thermal overload protection.
- Stainless steel screws.
- Cast iron switch case, motor and pump housing.
- Engineered, glass-filled impeller with metal insert (Model 53).
- Glass-filled polypropylene base. (Model 53).
- Model 57 all cast iron construction.
- UL listed 3-wire 15 ft. standard cord.



Canadian Standards
Assoc approval
available




TOTAL DYNAMIC HEAD/CAPACITY
PER MINUTE
EFFLUENT AND DEWATERING

53-55 MODELS			
Ft.	Meters	Gal.	Ltrs.
5	1.52	43	163
10	3.05	34	129
15	4.57	19	72
Lock Valve:		19.25'	

009897B

* Cast iron motor housing, pump housing and switch case.
Glass-filled polypropylene impeller and base.

"98" CAST IRON SERIES



Model BN98
Pictured

- BN/BE Models available packaged with a piggyback variable level float switch.
- 1/2 H.P., 1 Ph., 115V or 230V.
- Non-Clogging vortex impeller design.
- Passes 1/2 inch solids (sphere).
- 1 1/2" NPT discharge. (1 1/2" X 2" PVC adapter fitting included with BN and BE models.)
- Automatic reset thermal overload protection.
- Stainless steel screws, guard, handle.
- Watertight neoprene "□" ring between motor and pump housing.
- UL listed 3-wire 15 ft. standard cord.



Canadian Standards
Assoc approval
available




TOTAL DYNAMIC HEAD/CAPACITY
PER MINUTE
EFFLUENT AND DEWATERING

MODEL 98 60 CYCLE			
Feet	Meters	Gallons	Liters
5	1.5	72	273
10	3.1	61	231
15	4.6	45	170
20	6.1	25	95
Lock Valve:		23'	

009971B



"137" CAST IRON SERIES



Model BN137
Pictured

- BN/BE Models available packaged with a piggyback variable level float switch.
- Durable cast iron construction.
- 1 & 3 Phase models available.
(115, 200-208 & 230V - 1 Ph).
(200-208, 230 & 460V - 3 Ph).
- Non-Clogging vortex impeller design.
- Passes 5/8" solids (sphere).
- 1 1/2" NPT discharge. (1 1/2" X 2" PVC adapter fitting included with BN and BE models.)
- Automatic reset thermal overload protection.
- Stainless steel screws, bolts, guard, handle.
- UL listed 3-wire 15 ft. standard cord.



Canadian Standards
Assoc approval
available




TOTAL DYNAMIC HEAD/CAPACITY
PER MINUTE
EFFLUENT AND DEWATERING

MODELS 137			
Ft.	Meters	Gal.	Ltrs.
5	1.5	93	352
10	3.1	79	299
15	4.6	64	242
20	6.1	36	136
25	7.6	8	30
Lock Valve:		26'	

009921B

NOTE: No UL listing for 200-208/1Ph. pumps.



CAUTION Model 185/4185 should not be subjected to less than 30 feet TDH.

TOTAL DYNAMIC HEAD/
FLOW PER MINUTE
EFFLUENT AND DEWATERING

MODEL	53,55		98		137		140, 4140		161, 4161		163, 4163		165, 4165		185, 4185		186, 4186		188, 4188		189, 4189		191	
FT. M.	GAL.	LTRS.	GAL.	LTRS.	GAL.	LTRS.	GAL.	LTRS.	GAL.	LTRS.	GAL.	LTRS.	GAL.	LTRS.	GAL.	LTRS.	GAL.	LTRS.	GAL.	LTRS.	GAL.	LTRS.	GAL.	LTRS.
5 1.5	43	163	72	273	93	352	91	344	100	379	61	231	61	231			58	220	145	549	145	549	45	170
10 3.05	34	129	61	231	79	299	84	318	93	352	61	229	61	231			58	220	140	530	140	530	45	170
15 4.57	19	72	45	170	64	242	76	288	85	322	60	227	61	231			58	220	134	507	135	511	45	170
20 6.10			25	95	38	136	68	257	79	299	59	223	60	227			58	220	128	484	131	496	45	170
25 7.62					8	30	59	223	70	265	57	216	59	223			58	220	122	462	125	473	45	170
30 9.14							49	185	62	235	55	206	58	220	85	322	58	220	118	439	120	454	45	170
40 12.19							21	79	45	170	46	172	55	206	70	265	58	220	104	394	109	413	45	170
50 15.24									20	76	33	125	50	189	51	193	58	220	90	341	97	367	45	170
60 18.29											15	57	39	148	32	121	58	220	71	269	85	322	45	170
70 21.34													23	87	9	34	52	197	51	193	89	261	45	170
80 24.38													10	38			45	170	28	106	51	183	45	170
90 27.43																	31	117	2	8	34	129	45	170
100 30.48																	16	60			17	64	40	151
110 32.00																	4	15					30	114
120 36.58																							20	76
130 39.62																							10	38
LOCK VALVE:	19.25'		23'		26'		46'		56'		66'		86.5'		73'		114'		91'		110'		137'	



At-grade System Management Plan

Pursuant to Comm 83.54, Wis. Adm. Code

General

This system shall be operated in accordance with Comm 82-84 Wis. Adm. Code, and shall be maintained in accordance with its' component manuals [SBD-10570-P (R. 06/99) and SSWMP Pub. 9.6 (01/81)] and local or state rules pertaining to system maintenance and maintenance reporting.

No one should ever enter a septic or pump tank since dangerous gases may be present that could cause death.

Septic and pump tank abandonment shall be in accordance with Comm 83.33, Wis. Adm. Code when the tanks are no longer used as POWTS components.

Septic or pump tank manhole risers, access risers and covers should be inspected for water tightness and soundness. Access openings used for service and assessment shall be sealed watertight upon the completion of service. Any opening deemed unsound, defective, or subject to failure must be replaced. Exposed access openings greater than 8-inches in diameter shall be secured by an effective locking device to prevent accidental or unauthorized entry into a tank or component.

Septic Tank

The septic tank shall be maintained by an individual certified to service septic tanks under s. 281.48, Stats. The contents of the septic tank shall be disposed of in accordance with NR 113, Wis. Adm. Code. The operating condition of the septic tank and outlet filter shall be assessed at least once every 3 years by inspection.

The outlet filter shall be cleaned as necessary to ensure proper operation. The filter cartridge should not be removed unless provisions are made to retain solids in the tank that may slough off the filter when removed from its enclosure. If the filter is equipped with an alarm, the filter shall be serviced if the alarm is activated continuously. Intermittent filter alarms may indicate surge flows or an impending continuous alarm.

The septic tank shall have its contents removed when the volume of sludge and scum in the tank exceeds 1/3 the liquid volume of the tank. If the contents of the tank are not removed at the time of a triennial assessment, maintenance personnel shall advise the owner of when the next service needs to be performed to maintain less than maximum scum and sludge accumulation in the tank.

The addition of biological or chemical additives to enhance septic tank performance is generally not required. However, if such products are used they shall be approved for septic tank use by the Department of Commerce.

Pump Tank

The pump (dosing) tank shall be inspected at least once every 3 years. All switches, alarms, and pumps shall be tested to verify proper operation. If an effluent filter is installed within the tank it shall be inspected and serviced as necessary.

At-grade and Pressure Distribution System

No trees or shrubs should be planted on the at-grade. Plantings may be made around the at-grade's perimeter, and the at-grade shall be seeded and mulched as necessary to prevent erosion and to provide some protection from frost penetration. Traffic (other than for vegetative maintenance) on the at-grade is not recommended since soil compaction may hinder aeration of the infiltrative surface within the mound and snow compaction in the winter will promote frost penetration. Cold weather installations (October-February) dictate that the at-grade be heavily mulched as protection from freezing.

Influent quality into the at-grade system may not exceed 220 mg/L BOD₅, 150 mg/L TSS, and 30 mg/L FOG for septic tank effluent or 30 mg/L BOD₅, 30 mg/L TSS, 10 mg/L FOG, and 10⁴ cfu/100 mL for highly treated effluent. Influent flow may not exceed maximum design flow specified in the permit for this installation.

The pressure distribution system is provided with a flushing point at the end of each lateral, and it is recommended that each lateral be flushed of accumulated solids at least once every 18 months. When a pressure test is performed it should be compared to the initial test when the system was installed to determine if orifice clogging has occurred and if orifice cleaning is required to maintain equal distribution within the dispersal cell.

Observation pipes within the dispersal cell shall be checked for effluent ponding. Ponding levels shall be reported to the owner, and any levels above 4 inches considered as an impending hydraulic failure requiring additional, more frequent monitoring.

Contingency Plan

If the septic tank or any of its components become defective the tank or component shall be repaired or replaced to keep the system in proper operating condition.

If the dosing tank, pump, pump controls, alarm or related wiring becomes defective the defective component(s) shall be immediately repaired or replaced with a component of the same or equal performance.

If the at-grade component fails to accept wastewater or begins to discharge wastewater to the ground surface, it will be repaired or replaced in its' present location by increasing basal area if toe leakage occurs or by renovating the biologically clogged absorption and dispersal media, installing new piping, and replacing other components as deemed necessary to bring the system into proper operating condition.

See Page 8 of this plan for the name and telephone number of your local POWTS regulator and service provider.

At-grade System Maintenance and Operation Specifications

Service Provider's Name
POWTS Regulator's Name

Bowman Plumbing Inc.
Dunn County Zoning Office

Phone 715/235-4634
Phone 715/232-1401

System Flow and Load Parameters

Design Flow - Peak	450	gpd	Maximum Influent Particle Size	1/8	in
Estimated Flow - Average	300	gpd	Maximum BOD5	220	mg/L
Septic Tank Capacity	1,000	gal	Maximum TSS	150	mg/L
Soil Absorption Component Size	900	ft ²	Maximum FOG	30	mg/L
Type of Wastewater	Domestic		Maximum Fecal Coliform	>10E4	cfu/100 mL


Service Frequency

Septic and Pump Tank	Inspect and/or service once every 3 years
Effluent Filter	Inspect and clean at least once every 3 years
Pump and Controls	Test once every 3 years
Alarm	Should test monthly
Pressure System	Laterals should be flushed and pressure tested every 1.5 years
Mound	Inspect for ponding and seepage once every 3 years
Other	Initially filter should be checked yearly to determine cleaning schedule

Miscellaneous Construction and Materials Standards

1. Observation pipes are slotted and materials conform to Table Comm 84.30-1, have a watertight cap, and are secured in as shown in the at-grade component manual.
2. Dispersal cell aggregate conforms to Comm 84.30 (6)(i), Wis. Adm. Code.
3. All gravity and pressure piping materials conform to the requirements in Comm 84, Wis. Adm. Code.
4. Tillage of the basal area is accomplished with a mold board or chisel plow.
5. The at-grade structure and other disturbed areas will be seeded and mulched to prevent soil erosion and help reduce frost penetration.
6. Areas within 15 feet of the downslope toe will be protected from compaction.
7. All other construction details are as per the at-grade component manual SBD-10570-P (R. 6/99).

Lateral Turn-up Detail



ORIGINAL**SOIL EVALUATION REPORT**Wisconsin Department of Commerce
Division of Safety and Buildings


in accordance with Comm 85, Wis. Adm. Code

1611
Page 1 of 3
Certified Soil Testing

Attach complete site plan on paper not less than 8½ x 11 inches in size. Plan must include, but not limited to: vertical and horizontal reference point (BM), direction and percent slope, scale or dimensions, north arrow, and location and distance to nearest road.

Please print all information.

Personal information you provide may be used for secondary purposes (Privacy Law, s. 15.04 (1) (m)).

County	Dunn
Parcel I.D.	
Reviewed By	Date
	10-14-02


Property Owner Smith, Bob	Property Location Govt. Lot SW 1/4 SE 1/4 S 25 T 29 NR 13 W
Property Owner's Mailing Address 768th Ave.	Lot # Block # Subd. Name or CSM#
City State Zip Code Phone Number Menomonie WI 54751 715-235-6451	<input type="checkbox"/> City <input type="checkbox"/> Village <input checked="" type="checkbox"/> Town Nearest Road Sherman 760Th Ave.

<input checked="" type="checkbox"/> New Construction Replacement	Use: <input checked="" type="checkbox"/> Residential / Number of bedrooms <u>3</u> <input type="checkbox"/> Public or commercial - Describe: _____	Code derived design flow rate <u>450</u> GPD
Parent material <u>loess over sandstone</u>		Flood plain elevation, if applicable <u>NA</u>
General comments and recommendations: install 7.5' x 120' effective (9.5' x 120' overall) rock at-grade system w/ laterals following 101.3 contour		

1	Boring # <input type="checkbox"/> Boring <input checked="" type="checkbox"/> Pit	Ground Surface elev. <u>101.3</u> ft.	Depth to limiting factor <u>40</u> in.	Soil Application Rate						
Horizon	Depth in.	Dominant Color Munsell	Redox Description Qu. Sz. Cont. Color	Texture	Structure Gr. Sz. Sh.	Consistence	Boundary	Roots	GPD/R²	
									*Eff#1	*Eff#2
1	0-4	10YR 3/2	-	sil	2 f sbk	mvfr	cs	1f/m	.5	.8
2	4-21	10YR 4/6	-	sil	2 m sbk	mvfr	gs	1f	.5	.8
3	21-26	10YR 4/6	-	sl	2 m sbk	mvfr	cs	1f	.5	.9
4	26-37	5Y 4/3	-	fs	0 sg	ml	cs	-	.5	.9
5	37-40	5Y 5/3	-	lfs	0 sg	ml	cs	-	.5	.9
6	40+			SSBR						
SSBR by resistance to penetration; weakly cemented										

2	Boring # <input type="checkbox"/> Boring <input checked="" type="checkbox"/> Pit	Ground Surface elev. <u>99.3</u> ft.	Depth to limiting factor <u>43</u> in.	Soil Application Rate						
Horizon	Depth in.	Dominant Color Munsell	Redox Description Qu. Sz. Cont. Color	Texture	Structure Gr. Sz. Sh.	Consistence	Boundary	Roots	GPD/R²	
									*Eff#1	*Eff#2
1	0-5	10YR 3/2	-	sil	2 f sbk	mvfr	cs	1f/m	.5	.8
2	5-11	10YR 4/3	-	sil	2 m sbk	mvfr	gs	1m	.5	.8
3	11-26	10YR 4/6	-	sil	2 m sbk	mvfr	cs	1m	.5	.8
4	26-35	10YR 4/6	-	sl	1 m sbk	mfr	cs	-	.4	.6
5	35-43	5Y 4/3	-	fs	0 sg	ml	cs	-	.5	.9
6	43+			SSBR						
some SS frag in horizon 4; SSBR by resistance to penetration; weakly cemented										

* Effluent #1 = BOD₅ > 30 ≤ 220 mg/L and TSS >30 ≤ 150 mg/L* Effluent #2 = BOD₅ ≤ 30 mg/L and TSS ≤ 30 mg/L

CST Name (Please Print) Henry F. Grote	Signature: 	CST Number 222774
Address Certified Soil Testing E. 4366 353rd Ave., Menomonie, WI 54751		Date Evaluation Conducted 8/24/2002
		Telephone Number 715-233-0398

3

Boring #

☐ Boring
☒ Pit

Ground Surface elev. 101.3 ft.
Depth to limiting factor 58 in.

Soil Application Rate

GPD/ft²

*Eff#1 *Eff#2

Horizon	Depth in.	Dominant Color Munsell	Redox Description Qu. Sz. Cont. Color	Texture	Structure Gr. Sz. Sh.	Consistence	Boundary	Roots	GPD/ft²	
									*Eff#1	*Eff#2
1	0-4	10YR 3/2	-	sil	2 f sbk	mvfr	cs	1f/m	.5	.8
2	4-18	10YR 4/4	-	sil	2 f-m sbk	mvfr	gs	1m	.5	.8
3	18-42	10Yr 4/4	-	sil	3 m sbk	mfr	gs	1m	.5	.8
4	42-51	10YR 4/4	-	sl	0 m	mfr	cs	1f	.3	.5
5	51-58	5Y 5/3	-	fs	0 sg	ml	cs	-	.5	.9
6	58+			SSBR						
occasional Ss frag in horizon 4; SSBR by resistance to penetration; weakly cemented										

Boring #

☐ Boring
☐ Pit

Ground Surface elev. _____ ft.
Depth to limiting factor _____ in.

Soil Application Rate

GPD/ft²

*Eff#1 *Eff#2

Horizon	Depth in.	Dominant Color Munsell	Redox Description Qu. Sz. Cont. Color	Texture	Structure Gr. Sz. Sh.	Consistence	Boundary	Roots	GPD/ft²	
									*Eff#1	*Eff#2

Boring #

☐ Boring
☐ Pit

Ground Surface elev. _____ ft.
Depth to limiting factor _____ in.

Soil Application Rate

GPD/ft²

*Eff#1 *Eff#2

Horizon	Depth in.	Dominant Color Munsell	Redox Description Qu. Sz. Cont. Color	Texture	Structure Gr. Sz. Sh.	Consistence	Boundary	Roots	GPD/ft²	
									*Eff#1	*Eff#2

Bob Smith - Plot Plan

N $\frac{1}{2}$ - SW - SE - 25 - 29 - 13 W


Town: Sharnan

- BM grade @ base of
lagged steel stake (100.0)
- backhoe pit
+ rod from elev
- des: ge contour (101.35)
- No 83 wet back problem
- All 4/6 > 100' 120 s. side


N

{ Scale 1" = 30' }

A horizontal number line with three tick marks. Below the first tick mark is the number 0. Below the second tick mark is the number 15. Below the third tick mark is the number 30.

Idy. F. 
45222774

Location Sketch



610945

3 br a. he
 slab on
 grade


unbroken
solid topography

page 3 of 3



National Brand

[illegible]



COUNTY OF DUNN
Dunn County Zoning Office
800 Wilson Avenue
Menomonie, Wisconsin 54751

Telephone (715) 232-1401

FAX: (715) 232-4099

Bob Smith
E5139 760th Ave.
Menomonie, WI 54751

RE: Parcel described as part of the SW of the SE, Section 25, T29N-R13W,
Town of SHERMAN, Dunn County, Wisconsin

Septic system installation address/fire number is -- E5139 760TH Ave.

Dear Private Sewage System Owner:

Last year, a new or replacement on-site waste disposal system was installed on the parcel described above. This installation was inspected for code compliance and the inspection report together with the installing plumbers original forms are on permanent file with this office.

Wisconsin Statutes (ss 145.245(3)) requires maintenance of the septic tank for sludge content every three years. You, or the subsequent owner of this property will be notified in the spring/summer of 2006 to perform maintenance on this system. This maintenance requirement will involve pumping of the septic tank by a licensed septic tank pumper, or an inspection which verifies no pumping is required at this time. This notification of maintenance will follow every three years thereafter. This maintenance requirement is binding on all successors and assigns of this parcel. As the present owner, you are asked to disclose this requirement to the new owner(s) prior to sale.

The purpose of this maintenance requirement is to avoid premature failure of the private sewage system. A failed system presents a very serious environmental health risk to you and others.


If you have any question about this maintenance program, please do not hesitate to contact this office.

Sincerely,

Michael Helgeson

Michael Helgeson
Zoning Administrator

MH/jr



Environmental Services Department

Land Conservation, Planning, Solid Waste
Surveying, and Zoning Divisions

Telephone: 715.231.6521

FAX: 715.232.4099

August 30, 2012

A private sewage system or replacement was installed on property you own during the year listed below. As per 145.245(3) Wisconsin State Statutes and Chapter 6 of the Dunn County Comprehensive Zoning Ordinance (1993), you are required to be contacted by the Dunn County Zoning Office informing you of your responsibility to provide maintenance on the system. This maintenance program requires inspection of or pumping of the private sewage system at least once every three years.

As per 83.54.4(d) 1. Except as provided in subparagraph 3, a POWTS that exists prior to July 1, 2000, and that utilizes a treatment or dispersal component consisting in part of in situ soil shall be visually inspected at least once every 3 years to determine whether wastewater or effluent from the POWTS is ponding on the surface of the ground.

Inspections shall be conducted by a licensed master plumber, licensed journeyman plumber, licensed restricted plumber or licensed septic tank pumper. The inspection shall certify that the system is in proper operating condition and the septic tank is less than 1/3 full of sludge and scum. If the inspection reveals sludge and scum volume to be greater than 1/3 the volume of the tank, the tank shall be serviced by a licensed septic tank pumper. You may choose to go directly to pumping the tank and eliminate the need for an inspection which determines if the tank needs pumping.

In either case, please return this letter within 45 days with the appropriate signatures. Septic tank maintenance will ensure maximum service life of your private sewage system and avoid premature failure and very costly replacement. **Filing of this signed letter will alert future buyers of this property, that required maintenance was or was not performed. This will be the only contact from this office.**

Inspection of the private septic system components reveal that it does require pumping at this time. Contact septic pumper for service. (PLEASE INDICATE IF PUMPING WAS COMPLETED BEFORE MAILING BACK THIS FORM)

Date of inspection _____

Signature of inspector and license number _____

I certify that the septic system on the property mentioned below is not ponding on the ground surface or backing up into the structure, and that the septic tank has been visually inspected and pumped. (To be completed by septic tank pumper only)

John Smith 2393

Date of pumping 10-16-12

Signature of septic tank pumper and license number _____

Inspection of the private septic system components reveal that the system does not require pumping at this time.

Date of inspection _____

Signature of inspector and license number _____

RETURN TO:

Dunn County Zoning Office

390 Red Cedar St. Suite C

Menomonie, Wisconsin 54751

432414

032 291325.40301

Year of installation


or replacement

2003

Lot/CSM/Sub. & Parcel Address

ROBERT C
SMITH
N7756 510TH ST
MENOMONIE WI 54751

N7756 510TH ST



Environmental Services Department

Land Assessment, Land conservation, Planning

Solid waste, Surveying, Zoning

Telephone: 715.231.6521

FAX: 715.232.4099

August 28, 2009

A private sewage system or replacement was installed on property you own during the year listed below. As per 145.245(3) Wisconsin State Statutes and Chapter 6 of the Dunn County Comprehensive Zoning Ordinance (1993), you are required to be contacted by the Dunn County Zoning Office informing you of your responsibility to provide maintenance on the system. This maintenance program requires inspection of or pumping of the private sewage system at least once every three years.

As per 83.54.4(d) 1. Except as provided in subparagraph 3, a POWTS that exists prior to July 1, 2000, and that utilizes a treatment or dispersal component consisting in part of in situ soil shall be visually inspected at least once every 3 years to determine whether wastewater or effluent from the POWTS is ponding on the surface of the ground.

Inspections shall be conducted by a licensed master plumber, licensed journeyman plumber, licensed restricted plumber or licensed septic tank pumper. The inspection shall certify that the system is in proper operating condition and the septic tank is less than 1/3 full of sludge and scum. If the inspection reveals sludge and scum volume to be greater than 1/3 the volume of the tank, the tank shall be serviced by a licensed septic tank pumper. You may choose to go directly to pumping the tank and eliminate the need for an inspection which determines if the tank needs pumping.

In either case, please return this letter within 45 days with the appropriate signatures. Septic tank maintenance will ensure maximum service life of your private sewage system and avoid premature failure and very costly replacement. **Filing of this signed letter will alert future buyers of this property, that required maintenance was or was not performed. This will be the only contact from this office.**

Inspection of the private septic system components reveal that it does require pumping at this time. Contact septic pumper for service.

Date of inspection _____

Signature of inspector and license number _____

I certify that the septic system on the property mentioned below is not ponding on the ground surface or backing up into the structure, and that the septic tank has been visually inspected and pumped. *(To be completed by septic tank pumper only)*

J. Muller #2387

Date of pumping Oct 6, 2009

Signature of septic tank pumper and license number _____

Inspection of the private septic system components reveal that the system does not require pumping at this time.

Date of inspection _____

Signature of inspector and license number _____

RETURN TO:

Dunn County Zoning Office

390 Red Cedar St. Suite C

Menomonie, Wisconsin 54751

Year of installation

or replacement

432414

032 291325.40301

2003

Lot/CSM/Sub. & Parcel Address

ROBERT C
SMITH
N7756 510TH ST
MENOMONIE WI 54751

N7756 510TH ST